



TYPICAL SECTIONS

| R.O.W | SL | OL | WL | GL | P | GR | WR | OR | SR |
|-------|------|------|----|-------|-----|-------|----|------|-------|
| 50' | 10.5 | 0.5' | 5' | 5' | 29' | 5' | 5' | 0.5' | 10.5' |
| 60' | 12' | 0.5' | 5' | 6.5' | 36' | 6.5' | 5' | 0.5' | 12' |
| 70' | 17' | 0.5' | 5' | 11.5' | 36' | 11.5' | 5' | 0.5' | 17' |

KEY

- O -OFFSET (SIDEWALK OFFSET FROM PROPERTY LINE)
- W -SIDEWALK (S/W)
- G -GRASS STRIP
- S -SHOULDER
- P -PAVEMENT WIDTH
- PL -PROPERTY LINE

NOTES:

1. SLOPE OF PAVEMENT FROM CENTERLINE TO GUTTER SHALL BE 1/4"=1'
2. SUBGRADE TO BE PREPARED IN ACCORDANCE WITH VDH&T ROAD AND BRIDGE SPECIFICATIONS.
3. FINAL PAVEMENT SECTION WILL BE PREDICATED ON APPROVAL OF DESIGN BASE ON THE LATES VDOT PAVEMENT DESIGN GUIDE.

STREET SECTION



TOWN OF VIENNA, VIRGINIA
DEPARTMENT OF PUBLIC WORKS

DRAWING NO.
N/A
SCALE
N.T.S
SHEET
1 of 1

| | |
|---------------|------------|
| DATE/REVISION | |
| | 2015/01/08 |
| | 2010/11/13 |